

Y22 : WINDOWS, DOORS & DOORWAYS			Mat.	Lab.	Plant	Total
			£	£	£	£
Y2220						
040	Forming new double door opening through block wall Cutting to form openings through 100 mm block wall 1200 x 2000 mm, insert precast prestressed concrete lintel 65 mm deep, wedging and pinning to underside of existing construction, forming square jambs and sills (C2010/640 - 1 nr)	nr	24.21	211.47	11.95	247.63
045	Forming new double door opening through metal or timber stud partition Cutting to form openings through 100 mm stud partition 800 x 2000 mm, inserting studs at head and jambs, making good structure, making good finishings (C2010/675 - 1.5 nr)	nr	29.07	94.97		124.04
Y2230	WIDENING EXISTING DOORWAYS					
100	Widen existing single doorway in masonry wall up to 250mm thick Cutting to form openings through 215 mm brick wall ne 0.50 m2 (C2010/595 - 1 nr), Cutting out defective precast reinforced concrete internal lintel and renewing with 150 x 100 x 1000 mm long precast concrete lintel (C4005/050 - 1 nr), Stripping off/removing/taking down doors in preparation for replacement (C5170/800 - 1 nr), Stripping off/removing/taking down door frames and linings, making good finishings in preparation for replacement (C5170/818 - 1 nr), Walls ne 300 mm wide to brickwork, blockwork or stonework (M2025/100 - 6 m), Bonding/jointing new to existing (M2025/150 - 6 m)	nr	20.65	254.59	14.95	290.19
105	Widen existing single doorway in blockwork wall Cutting to form openings through 100 mm block wall ne 0.50 m2 (C2010/605 - 1 nr), Cutting out defective precast reinforced concrete internal lintel and renewing with 150 x 100 x 1000 mm long precast concrete lintel (C4005/050 - 1 nr), Stripping off/removing/taking down doors in preparation for replacement (C5170/800 - 1 nr), Stripping off/removing/taking down door frames and linings, making good finishings in preparation for replacement (C5170/818 - 1 nr), Walls ne 300 mm wide to brickwork, blockwork or stonework (M2025/100 - 6 m), Bonding/jointing new to existing (M2025/150 - 6 m)	nr	20.65	237.98	10.04	268.67
110	Widen existing single doorway in metal or timber stud partition wall Cutting to form openings through stud partition ne 0.50 m2 (C2010/670 - 1 nr), Stripping off/removing/taking down doors in preparation for replacement (C5170/800 - 1 nr), Stripping off/removing/taking down door frames and linings, making good finishings in preparation for replacement (C5170/818 - 1 nr), Wall or partition members 50 x 75 mm (G2010/122 - 3 m)	nr	16.04	45.47		61.51
© NSR 01 Aug 2008 - 31 Jul 2009			Y41			

Y22 : WINDOWS, DOORS & DOORWAYS			Mat.	Lab.	Plant	Total
			£	£	£	£
Y2230						
115	<p>Widen existing double doorway in masonry wall up to 250mm thick</p> <p>Cutting to form openings through 215 mm brick wall ne 0.50 m2 (C2010/595 - 1 nr), Cutting out defective precast reinforced concrete internal lintel and renewing with 150 x 100 x 2000 mm long precast concrete lintel (C4005/055 - 1 nr), Stripping off/removing/taking down doors in preparation for replacement (C5170/800 - 2 nr), Stripping off/removing/taking down door frames and linings, making good finishings in preparation for replacement (C5170/818 - 1 nr), Walls ne 300 mm wide to brickwork, blockwork or stonework (M2025/100 - 8 m), Bonding/jointing new to existing (M2025/150 - 8 m)</p>	nr	30.97	305.54	16.24	352.75
120	<p>Widen existing double doorway in blockwork wall</p> <p>Cutting to form openings through 100 mm block wall ne 0.50 m2 (C2010/605 - 1 nr), Cutting out defective precast reinforced concrete internal lintel and renewing with 150 x 100 x 2000 mm long precast concrete lintel (C4005/055 - 1 nr), Stripping off/removing/taking down doors in preparation for replacement (C5170/800 - 1 nr), Stripping off/removing/taking down door frames and linings, making good finishings in preparation for replacement (C5170/818 - 1 nr), Walls ne 300 mm wide to brickwork, blockwork or stonework (M2025/100 - 8 m), Bonding/jointing new to existing (M2025/150 - 8 m)</p>	nr	30.97	283.17	11.33	325.47
125	<p>Widen existing double doorway in metal or timber stud partition wall</p> <p>Cutting to form openings through stud partition ne 0.50 m2 (C2010/670 - 1 nr), Stripping off/removing/taking down doors in preparation for replacement (C5170/800 - 2 nr), Stripping off/removing/taking down door frames and linings, making good finishings in preparation for replacement (C5170/818 - 1 nr), Wall or partition members 50 x 75 mm (G2010/122 - 4 m)</p>	nr	19.87	54.40		74.27
Y2240	BLOCK UP EXISTING DOORWAYS					
150	<p>Block up existing single door opening in internal masonry wall 215mm thick; plastered both sides; decorated.</p> <p>Filling in openings 900 x 2000 x 215 mm thick, bonding and wedging and pinning to existing (C2065/854 - 1 nr), Timber skirtings, 25 x 100 mm, cutting out mid-section ne 1 m long replacing with new jointed to existing (C5105/135 - 2 nr), Stripping off/removing/taking down doors in preparation for replacement (C5170/800 - 1 nr), Stripping off/removing/taking down door frames and linings, making good finishings in preparation for replacement (C5170/818 - 1 nr), Walls over 300 mm wide to brickwork, blockwork or stonework 1 to 5 m2 (M2025/051 - 4 m2), Bonding/jointing new to existing (M2025/150 - 6 m), Plaster general surfaces over 300 mm girth (M6015/140 - 4 m2)</p>	nr	101.14	361.53	1.96	464.63